



Material Safety Data Sheet
ZeraDur Line Paint- Zone Yellow PART A

PRODUCT INFORMATION

Manufacturer: Zeraus Products Inc.
250 Rayette Road, Unit 18
Vaughan, Ontario L4K 2G6

PRODUCT INFORMATION

Product Identifier: ZeraDur Line Paint Yellow Part A

Application and Use: Epoxy Floor Coating

Product Description: Two-component 100% solids Epoxy Line Paint (epoxy resin blend)

HAZARD RATING SYSTEM (USA):

Health: 2

Flammability: 1

Reactivity: 0

WHMIS Classification (Canada):

Class D, Division 2, Subdivision B: irritant

TRANSPORTATION OF DANGEROUS GOODS INFORMATION:

Not Regulated

EMERGENCY TELEPHONE NUMBERS

Business: (905) 761-9920

24 Hours: (416) 574-5154

LABEL PRECAUTIONS

NOT REGULATED. HARMFUL IF SWALLOWED OR INHALED. MILD SKIN AND EYE IRRITANT.

Keep container closed.

Use only with adequate ventilation

Wash thoroughly after handling

Avoid breathing vapours

Avoid contact with eyes, skin and clothing

Keep away from children

Do not dispose down the drains

HAZARD INGREDIENTS

Ingredients	CAS#	%(weight)	LD/50 Route/Species
Diglycidyl Ether of Bisphenol-A	25068-38-6	60-100	30g/kg/Oral/rat
2-Methylphenyl Glycidyl Ether	2210-79-9	1-5	4000mg/kg(Rat-Oral) >2000mg/kg(Rabbit-Skin)
Dibutyl Phthalate 2500mg/kg(Rabbit-Dermal)	84742	1-5	8000mg/kg(Rat-Oral)

Lead Sulphochromate Yellow

1344-37-2

1-10%

LD50- (Rat-Oral)

>2000 mg/Kg

PHYSICAL DATA

Physical State: Liquid
Specific Gravity: 1.65
Solubility in Water: Insoluble
Boiling Point: n/av
Freezing/Melting Point: n/av
Viscosity: 3000 cps @ 23°C (73°F)

Evaporation Rate: n/av
Volatile: (voc): less than 1 %
Vapour Density: n/av
Odour: pleasant citric odour
Appearance: Coloured Liquid
Hazardous Air Pollutants: none

POTENTIAL HEALTH EFFECTS

Effect of Overexposure:

INHALATION: Do not heat the material. Vapours or mist generated from heating the material or as from exposure in poorly ventilated areas are irritating and cause nasal discharge. Coughing and discomfort in nose and throat. Prolonged or repeated overexposure may result in lung damage.

EYES: Cause irritation, experienced as pain, with excess blinking and tear production

SKIN: Causes skin irritation. It may cause skin sensitization.

INGESTION: Acute (brief exposure): Low toxicity causes irritation. Chronic (prolonged exposure): causes burning of mouth, throat, and stomach, nausea, vomiting, and diarrhea.

INGESTION: CHRONIC: Refer to acute ingestion.

Toxic effects or reproduction: No
Teratogenicity: No
Mutagenicity: No
Carcinogenicity: No

Acute or chronic exposure should be avoided as it will increase the toxicological problems mentioned in this section and may aggravate respiratory problems. Repeated skin contact may cause a persistent irritation or dermatitis. Repeated inhalation may cause lung damage.

FIRST AID MEASURES

Emergency procedures:

INHALATION: In the case of overexposure, remove to fresh air. Get medical attention if the victim is in respiratory distress.

EYE CONTACT: Flush eyes immediately with large amounts of running water for at least 15 minutes while holding eyelids open until irritation subsides. Do not attempt to neutralize with chemical agents. Obtain medical attention immediately.

SKIN CONTACT: Wash immediately with plenty of soap and water. Remove and clean all contaminated clothing and laundry before reuse.

INGESTION: If swallowed, drink two glasses of water. Do not induce vomiting. The material is corrosive. Do not give anything to mouth to an unconscious person. Get prompt medical attention.

PREVENTIVE MEASURES

PERSONAL PROTECTION: The selection of personal protective equipment varies depending upon conditions of use. When handling product wear long sleeves, chemical resistant gloves and safety glasses with side shields. Where splashing during mixing may occur wear full face shield. Where concentrations in air may exceed the occupational exposure limits and where engineering work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation. The respirators may not be necessary for handling the materials in outdoor environment. Eye wash station (sink) or shower facility near the job is recommended in case of emergency.

ACCIDENTAL RELEASE MEASURES

PROCEDURE IN CASE OF LEAKS:

Prevent spills from entering sewers, watercourses or low areas. Absorb with sand or other absorbent material. Residue may be removed with hot water and detergent. All precautions should be taken when cleaning the spill with solvent.

ENVIRONMENTAL PRECAUTIONS: Avoid discharge to sewers or waterways.

SPILL CONTROL AND DISPOSAL: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.

HANDLING AND STORAGE

HANDLING STORAGE AND SHIPPING: Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. Do not handle or store near an open flame, sources of heat, or sources of ignition. Protect material from direct sunlight. This product will accumulate static charges which may cause an incendiary electrical discharge. Use proper grounding procedures. Empty product containers may contain product residue. DO NOT REUSE.

FIRE AND EXPLOSION DATA

Flashpoint and Method: 141 C (T.C.C.)
Auto ignition Temperature: Not applicable
Flammable Limits: Not Available

GENERAL HAZARDS: Combustible liquid; may release vapours that form combustible mixtures at or above the flash point. Toxic gases will form upon combustion.

FIRE FIGHTING: Wear NIOSH-approved self-contained breathing apparatus with independent air supply. Wear complete body protective butyl rubber clothing. Personnel in vicinity and downwind should be evacuated.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, and carbon monoxide, various hydrocarbons, phenol.

REACTIVITY DATA

GENERAL: This product is stable and hazardous polymerization will not occur under normal conditions.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: Excessive heating. Avoid contact with strong acids and alkalis.

HAZARDOUS DECOMPOSITION: carbon monoxide



**Material Safety Data Sheet
ZeraDur Line Paint- Zone Yellow PART B**

PRODUCT INFORMATION

Manufacturer: Zeraus Products Inc.
250 Rayette Road, Unit 18
Vaughan, Ontario L4K 2G6

PRODUCT INFORMATION

Product Identifier: ZeraDur Line Paint Yellow Part B
Application and Use: Epoxy Floor Coating
Product Description: Two-component 100% solids Epoxy Line Paint (Amine curative)

HAZARD RATING SYSTEM (USA):

Health: 3
Flammability: 1
Reactivity: 0

WHMIS Classification (Canada):

Class D-2B
Class E, corrosive

TRANSPORTATION OF DANGEROUS GOODS INFORMATION:

Amines, liquid, Corrosive, N.O.S. (Benzene, 1-3-Dimethaneamine)
Hazard Class: 8
ID Number: UN 2735
Packing Group: II

EMERGENCY TELEPHONE NUMBERS

Business: (905) 761-9920 24 Hours: (416) 574-5154

LABEL PRECAUTIONS

CORROSIVE MATERIAL. HARMFUL IF SWALLOWED. TOXIC BY INHALATION. CAN CAUSE EYE AND SKIN BURN. MAY CAUSE SENSITIZATION.

- Keep container closed.**
- Use only with adequate ventilation**
- Wash thoroughly after handling**
- Avoid breathing vapours**
- Avoid contact with eyes, skin and clothing**
- Keep away from children**

HAZARD INGREDIENTS

Benzyl Alcohol	100-51-6	30-60
Benzene-1,3-Dimethaneamine (MXDA)	1477-55-0	15-30
Isophron Diamine (IPD)	2855-13-2	15-30
Epoxy Polyamine Adduct		10-30

PHYSICAL DATA

Physical State: Liquid
Specific Gravity: 0.97
Vapour Pressure: n/av
Solubility in Water: Slight
Boiling Point: n/av
Freezing/Melting Point: n/av

Viscosity: 100 cps 23°C (73°F)
Vapour Density: n/av
Evaporation Rate: n/av
Volatile: (voc): 70%
Odour: Characteristic amine odour
Appearance: Clear
Hazardous Air Pollutant: None

POTENTIAL HEALTH EFFECTS

Effect of Overexposure:

INHALATION: Harmful if inhaled, may affect the nervous system, causing dizziness, headache, or nausea. May cause lung irritation. May cause allergic respiratory reaction.

EYE CONTACT: can cause eye burns.

SKIN CONTACT: can cause skin burns. Can cause allergic skin reaction and sensitization.

INGESTION: Swallowing may cause severe burns to the mouth, throat and stomach. May cause vomiting, nausea and dizziness. Loss of consciousness may occur. Drowsiness may occur. Weakness and incoordination may occur.

Toxic effects or reproduction:	No
Teratogenicity:	No
Mutagenicity:	No
Carcinogenicity:	No

Acute or Chronic Exposure: Repeated and/or prolonged exposure may cause allergic reaction/sensitization. Repeated and/or prolonged exposures may result in adverse eye effects, adverse skin effect. Dryness of nasal passages may be experienced when material is inhaled over a long period of time.

FIRST AID MEASURES

Emergency procedures:

In the event of an emergency, remove the victim from further exposure, send for medical assistance, and initiate the following emergency procedures:

INHALATION: If inhaled, remove victim to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention.

EYE CONTACT: Flush with water for at least 15 minutes while forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissue. Get medical attention. If medical care is not promptly available, continue to irrigate for one hour.

SKIN CONTACT: Immediately remove contaminated clothing. Wash with soap and water and maintain gentle and continuous irrigation for 15 minutes. Launder contaminated clothing before reuse. Contact a physician if irritation develops.

INGESTION: Give two glasses of water. Get medical attention immediately. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

NOTE TO PHYSICIAN: There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and as the clinical condition of the patient.

PREVENTIVE MEASURES

PERSONAL PROTECTION: The selection of personal protective equipment varies depending upon conditions of use. When handling product wear long sleeves, chemical resistant gloves and safety glasses with side shields. Where splashing during mixing may occur wear full face shield. Where concentrations in air may exceed the occupational exposure limits and where engineering work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation. The respirators may not be necessary for handling the materials in outdoor environment. Eye wash station (sink) or shower facility near the job is recommended in case of emergency.

ACCIDENTAL RELEASE MEASURES

PROCEDURE IN CASE OF LEAKS:

Extinguish and eliminate source of ignition until area is determined to be free from explosion or fire hazards. Prevent spills from entering sewers, watercourses or low areas. Absorb with sand or other absorbent material (do not use sawdust). Residue may be removed with hot water and detergent. Flush small spills with water.

ENVIRONMENTAL PRECAUTIONS: The product is toxic to aquatic life in liquid form. Avoid discharge to sewers or waterways. Marine Pollutant (Very toxic to aquatic organisms)

SPILL CONTROL AND DISPOSAL: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.

HANDLING AND STORAGE

HANDLING STORAGE AND SHIPPING: Keep container closed. Wear personal protective equipment. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. Keep away from heat, sparks, open flames and oxidizing agent. Protect material from direct sunlight. This product will accumulate static charges, which may cause an incendiary electrical discharge. Use proper grounding procedures. Empty product containers may contain product residue. **DO NOT REUSE.**

FIRE AND EXPLOSION DATA

Flashpoint and Method: 110 °C (T.C.C.)

GENERAL HAZARDS: Flammable liquid; may release vapour that form combustible mixtures at or above the flash point. Toxic gases will form upon combustion.

FIRE FIGHTING: Personnel in vicinity and downwind should be evacuated. Fire fighters should wear approved self contained breathing apparatus and full protective clothing.

HAZARDOUS COMBUSTION PRODUCTS: May generate toxic or irritating combustion products. Ammonia, carbon monoxide and/or carbon dioxide and oxides of Nitrogen.

REACTIVITY DATA

GENERAL: This product is stable and hazardous polymerization will not occur under normal storage conditions.

INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID: Excessive heating, sparks and open flames. Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION: Irritating and toxic fumes at elevated temperatures. Ammonia when heated. Oxides of nitrogen. Organic acid vapours. Nitric acid. Nitrosamines. Nitrogen oxides can react with water vapours to form corrosive nitric acid. Carbon monoxide and/or dioxide. May generate ammonia gas.

PREPARATION

Prepared By: A. Zaghloul
Zeraus Products Inc.
250 Rayette Road, Unit 18
Vaughan, Ontario L4K 2G6
April 2011

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. User should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Zeraus Products Inc. be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Zeraus Products Inc. has been advised of the possibility of such damages.