



ZeraCroma™ W

Coloured-Grade Waterborne Asphalt Sealer

DESCRIPTION

ZeraCroma™ W is based on a unique natural oil-based alkyd/acrylic hybrid latex technology. It produces a durable coating with a good cure speed and film toughness.

ZeraCroma™ W is offered in several highly attractive stylish earth colours that is designed to bring new life to asphalt pavement.

ZeraCroma™ W has superior chemical resistance as compared to standard styrene acrylic emulsion chemistries. It protects against penetration by petroleum products, making surfaces easier to clean.

RECOMMENDED FOR:

Asphalt surfaces in both indoor and outdoor applications such as driveways, tennis courts and parking garages.

BENEFITS

- Odourless and safe, non-toxic
- Attractive semi-gloss finish
- Easy to apply using a brush, roller or an airless spray
- Excellent adhesion to asphalt
- Outstanding colour stability and brightness
- Resistant to gasoline, oil, brake fluid and anti-freeze
- Resistant to hot-tire pickup
- Best combination of dry time and flexibility

Colours:

Offered only in white; other customs colours may be available based on a minimum orders and lead time.

SURFACE PREPARATION

ZeraCroma™ W is recommended to apply 5 weeks after new asphalt installation. This is to eliminate the oily materials that may impair the adhesion. It should be applied over a clean, sound and dust free surface.

MIXING AND APPLICATION

The mixing equipment used to mix the coating must be clean and free of any contaminants that may be present in the equipment from previously used products. Mix **ZeraCroma™ W** to eliminate the possibility of settlement.

Pour enough material onto the paint tray and apply with a 9 mm lint free roller. Apply evenly in a uniform fashion to provide an even film thickness of 8 mils in a single application. Allow to dry for 5 hours and reapply. Allow it to sufficiently cure prior to traffic.

LIMITATIONS

- Minimum application and curing temperature is 12°C (54°F)
- Must be applied to properly clean surfaces
- Avoid puddling or applying the coating in a thick film as it may cause shrinkage, cracking, and poor adhesion
- This sealer will not prevent cracking, breaking up and in some cases delamination of portions of asphalt surfaces.

COVERAGE

4.8 m²/L (200 ft²/U.S. gallon per coat)

PACKAGING

18.9 litres (5 U.S. gal)

CLEAN UP

Clean all equipment with potable water prior to dry.

SAFETY PRECAUTIONS:

- Keep container closed and away from children
- Use only with adequate ventilation
- Wash hands thoroughly after handling
- Avoid breathing vapours
- Avoid contact with eyes, skin and clothing
- Do not dispose down drains or sewers

- When handling product wear long sleeves, latex gloves and safety glasses

Emergency procedures:

INHALATION: In the case of overexposure, remove to fresh air. Get medical attention immediately if in respiratory distress.

EYE CONTACT: Flush eyes immediately with large amounts of running water for at least 15 minutes while holding eyelids open until irritation subsides. Obtain medical attention immediately.

SKIN CONTACT: Wash immediately with plenty of soap and water. Remove and clean all contaminated clothing and launder before reuse.

INGESTION: If swallowed, drink two glasses of water. Do not induce vomiting. Do not give anything to the mouth of an unconscious person. Get prompt medical attention.

WARRANTY

The recommendations made and the information herein is the result of accurate laboratory and field tests under controlled conditions. We guarantee that the quality and properties of the materials supplied conform to our standards. Zeraus Products Inc. makes no warranties, expressed or implied, as uses and applications are beyond our control. Zeraus Products Inc. shall not be liable for any injury, loss, or damage (direct or consequential) arising from use or inability to use the products. Before using, the user is urged to pre-test the products in his/her own environment to determine the suitability of the products for their intended use, and the user assumes all risk and liability whatsoever in connection therewith.

Zeraus Products Inc.'s liability, if any, is limited to a refund of the purchased price or replacement of that portion of the merchandise proven to be defective. Zeraus Products Inc. shall have no other liability, including liability for incidental, consequential or resultant damages, however caused, whether due to breach of warranty, negligence, or strict liability.

This warranty may not be modified or extended by representatives of Zeraus Products Inc., its distributors or dealers.